

Citrix

1Y0-351 Exam

Citrix NetScaler 10.5 Essentials and Networking Exam

Thank you for Downloading 1Y0-351 exam PDF Demo

You can Buy Latest 1Y0-351 Full Version Download

https://www.certkillers.net/Exam/1Y0-351

Version: 9.0

_				- •			_
<i>,</i>		\sim	•	-	\sim	•	7
Q		_	•			 	
~	·	·	J	•	J	••	_

A NetScaler Engineer has created a new custom user monitor script and needs to place it in the NetScaler filesystem for use.

Where must the engineer place the custom script so that it is available for use?

- A. /nsconfig/monitors
- B. /netscaler/monitors
- C. /var/nstemp/monitors
- D. /netscaler/monitors/perl_mod

Answer: A

Question: 2

What are the supported protocols for management authentication?

- A. LOCAL, LDAP, and SAML
- B. RADIUS, LDAP and TACACS+
- C. CERTIFICATE, LDAP and SAML
- D. RADIUS, TACACS+ and CERTIFICATE

Answer: B

Question: 3

Scenario: A NetScaler Engineer has discovered that the object home.php is NOT found in the cache on the system.

Below is the relevant configuration:

add cache contentGroup cache content group 1-relExpiry 0

add cache policy cache_pol_1 -rule "http.REQ.URL.CONTAINS(\"home.php\")" -action MAY_CACHE - storeInGroup cache_content_group_1

add cache policy cache_pol_2 -rule "http.REQ.METHOD.EQ(\"GET\")" -action NOCACHE add cache policy cache_pol_3 -rule "HTTP.RES.HEADER(\"Set-Cookie\").EXISTS" -action NOCACHE bind cache global cache_pol_1 -priority 90 -gotoPriorityExpression END -type REQ_OVERRIDE bind cache global cache_pol_2 -priority 100 -gotoPriorityExpression END -type REQ_OVERRIDE bind cache global cache_pol_3 -priority 100 -gotoPriorityExpression END -type RES_OVERRIDE The data from the client and the server are as following:

GET /home.php HTTP/1.1 Host: www.website.com

User-Agent: Mozilla Firefox/3.0.3

Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8

Accept-Language: en-us,en;q=0.5 Accept-Encoding: gzip,deflate

Accept-Charset: ISO-8859-1,utf-8;q=0.7,*;q=0.7

Keep-Alive: 300

Connection: keep-alive

Date: Thu, 09 Oct 2014 18:25:00 GMT

Cookie: sessionid=100xyz

HTTP/1.1 200 OK

Date: Thu, 09 Oct 2014 18:25:00 GMT Server: Apache/2.2.3 (Fedora)

Last-Modified: Wed, 09 Jul 2014 21:55:36 GMT

ETag: "27db3c-12ce-5e52a600"

Accept-Ranges: bytes

Cache-Control: private, max-age=0

Set-Cookie: sessionid=100xyz; expires=Thu, 09-Oct-2014 18:30:00 GMT; path=/

Content-Length: 119 Connection: close

Content-Type: text/html; charset=UTF-8 Why does the object NOT persist in the cache?

- A. The request is a GET request.
- B. The response has Set-Cookie.
- C. The content group is missing a cache selector.
- D. The content group has been configured with relExpiry 0.

Answer: B

Question: 4

Which two authentication types on the NetScaler support password changes? (Choose two.)

- A. TACACS+
- B. LDAP (TLS)
- C. LDAP (SSL)
- D. RADIUS (PAP)
- E. LDAP (PLAINTEXT)
- F. RADIUS (MSCHAPv2)

Answer: B,C

Question: 5

Scenario: A NetScaler Engineer is viewing Authentication, Authorization and Access (AAA) events on the NetScaler appliance to determine why a user is unable to log on. The events below have been logged during this timeframe:

Fri Oct 17 18:17:16 2014

/usr/home/build/rs_80_48/usr.src/usr.bin/nsaaad/../../netscaler/aaad/ldap_drv.c[40\]:

start_ldap_auth attempting to
auth scottli @ 10.12.33.216
Fri Oct 17 18:17:18 2014
/usr/home/build/rs_80_48/usr.src/usr.bin/nsaaad///netscaler/aaad/ldap_drv.c[291\]:
recieve_ldap_bind_event receive ldap bind event
Fri Oct 17 18:17:18 2014
/usr/home/build/rs_80_48/usr.src/usr.bin/nsaaad///netscaler/aaad/ldap_drv.c[326\]: recieve_ldap_bind_event ldap_bind with binddn bindpw failed:Invalid credentials Fri Oct 17 18:17:18
2014 /usr/home/build/rs 80 48/usr.src/usr.bin/nsaaad///netscaler/aaad/naaad.c[1198\]:
send_reject sending reject to kernel for : scottli
What is the root cause of this issue?
A The IDAD Beer DNI's in const
A. The LDAP Base DN is incorrect. B. The Bind DN credentials are invalid.
C. The LDAP server is NOT responding.
D. The user has entered an invalid password.
Answer: B
Question: 6
A company has an external-facing web application that requires end-to-end encryption and Layer-7
functionality.
Which protocol type would an engineer choose for the virtual server and service?
A. SSL
B. SSL_TCP
C. SSL_PUSH
D. SSL_BRIDGE

Question: 7

Scenario: A NetScaler Engineer has enabled the HTTP Compression feature on an existing production NetScaler. The engineer is using the built-in policies. The engineer reviews the HTTP Compression statistics but does NOT see any compression statistic data.

What is the likely reason?

- A. SSL protocol is being used for encryption.
- B. The Compression Policy engine is set to default.
- C. "Allow Server side compression" is checked on the NetScaler.
- D. Responses with the Content-Length or Chunked header are being sent from the server.

Answer: C

Answer: B

Answer: C,D

Question: 8
Which two of the listed statements are true about Access Control Lists (ACLs) on the NetScaler? (Choose two.)
A. Extended ACLs may BRIDGE traffic. B. Simple ACLs are bound on ALL interfaces. C. Extended ACLs are evaluated after creation.
D. Simple ACLs are processed after Extended ACLs.
Answer: A,B
Question: 9
What is the purpose of the SSL Certificate Authority (CA) root certificate during an SSL connection?
A. SSL Cipher Exchange B. Session Key Exchange C. Pre Shared Master Secret Generation D. Server Certificate Signature Verification
Answer: A
Question: 10
In order to create a three-node NetScaler cluster, all nodes must and (Choose the two correct options to complete the sentence.)
A. be physical appliances B. have Platinum licensing C. be using the same build

Question: 11

D. be the same platform model

Scenario: A NetScaler Engineer has been tasked with reconfiguring an existing NetScaler deployment. The engineer is currently running a high-availability (HA) pair of NetScaler 10.5 appliances, but the Vice President of IT has requested a more efficient way of preserving and balancing network resources and throughput while having a single point of management for the NetScaler appliances.

What should the engineer configure to satisfy the requirements outlined by the Vice President of IT?

- A. Switch from traditional HA to -INC mode HA.
- B. Break the HA pair and configure clustering instead.

	e three standalone NetScaler nodes. bandwidth to both NetScaler nodes.	
		Answer: B
Question: 12		
configuration auditing by using NI	deploy a third-party application of TRO API with a REST interface. Ild the engineer enable to allow NITR	
A. SSH B. HTTP C. Telnet D. SNMP		
		Answer: B
Question: 13		
Traffic to which destination is sour	ced from the NetScaler IP (NSIP) by d	lefault?
A. NTP serversB. Clients on the InternetC. Load-balanced web servicesD. Load-balanced authentication s	ervices	
		Answer: A
Question: 14		
named 'myApp'. Many clients do I fail as a result. All clients are beh the client IP address into an HTTP Which command could the engine the requests across the bound ser A. set Ib vserver myApp -persisten B. set Ib vserver myApp -persisten C. set Ib vserver myApp -persisten	eer execute to provide persistence fo vices? ceType SOURCEIP ceType NONE -lbmethod SRCIPDESTI ceType COOKIEINSERT -timeout 0 -co	pe set and application sessions IAT) gateway, which will insert r clients while still distributing PHASH pokieName X-Forwarded-For
Forwarded-For\").VALUE(0)	enceType NONE -lb method TOKEN	-rule HTTP.KEQ.HEADEK(\"X-
		Answer: D

Question: 15
Scenario: A NetScaler Engineer has created an SSL virtual server that utilizes SSL services. The engineer needs to configure certificate authentication from the NetScaler to the backend web services. What should the engineer do to meet the requirements outlined in the scenario?
 A. Bind a CA Certificate to the SSL Services. B. Bind a Client Certificate to the SSL Services. C. Create an SSL policy to present the Client Certificate to the web services. D. Enable Client Authentication and set Client Certificate to mandatory on the virtual server.
Answer: B
Question: 16
Which service setting would a NetScaler Engineer use in the command-line interface to limit connections to server resources?
AmaxReq BmaxClient CmonThreshold DmaxBandwidth
Answer: B
Question: 17
Which statement is true about interface link-state on the NetScaler?
 A. Interface link-state is controlled by ifconfig in BSD. B. Interface link-state is dependent on the HAMON setting. C. Interface link-state CANNOT be brought down from the NetScaler. D. Interface link-state on both appliances is unaffected by the force failover command.
Answer: C
Question: 18
In order to configure integrated cache, a NetScaler Engineer would need to reboot the NetScaler when the integrated caching feature is and cache memory limit is set to (Choose the correct set of options to complete the sentence.)
A. enabled; zero B. disabled; zero C. enabled; non-zero

D. disabled; non-zero	
	Answer: A
Question: 19	
Which two certificate formats are supported when creating a certificate (Choose two.)	te key pair on the NetScaler?
A. PEM B. DER C. PKCS7 D. PKCS12	
	Answer: A,B
Question: 20	
As a result of connecting two NetScaler interfaces in the same L2 brollink aggregation is configured), the NetScaler will (C complete the sentence.)	padcast domain/VLAN (unless hoose the correct option to
A. restart B. disable one interface C. cause a network loop D. disable both interfaces	
	Answer: C
Question: 21	
Scenario: Users in an organization need to access several web applications asked a NetScaler Engineer to reduce the amount of times users has accessing web applications. What should the engineer configure to meet this requirement?	
A. A load-balancing VServer and an authorization policyB. An authentication VServer and an authorization policyC. An authentication VServer and an authentication policyD. A content switching VServer and an authentication profile	
	Answer: C
Question: 22	
Question. 22	
The upgrade script copies the updated NetScaler kernel file to the	NetScaler directory.

(Choose the correct option to complete the sentence.)	
A. /var B. /flash C. /nsconfig D. /flash/boot	
	Answer: B
Question: 23	
Which setting must an engineer ensure is configured before a Subrommunicate with servers on the same network segment?	net IP (SNIP) could be used to
A. Static route is defined	
B. USIP mode is enabled C. USNIP mode is enabled	
D. Default gateway is defined	
	Answer: C
Question: 24	
Which tool could a NetScaler Engineer use to monitor client-side application that is load-balanced by NetScaler?	e rendering times for a Web
A. Tcpdump B. Insight Center C. Command Center D. NetScaler Dashboard	
	Answer: A
Question: 25	
What should a NetScaler Engineer configure to create load-balancing the same VLAN with overlapping IP addresses?	virtual servers and services on
A. Listen policies	
B. Traffic domains C. Dynamic routing	
D. Policy-based routing	
	Answer: B

Thank You for trying 1Y0-351 PDF Demo

To Buy Latest 1Y0-351 Full Version Download visit link below

https://www.certkillers.net/Exam/1Y0-351

Start Your 1Y0-351 Preparation

[Limited Time Offer] Use Coupon "CKNET" for Further discount on your purchase. Test your 1Y0-351 preparation with actual exam questions.